HAZUS-MH: Earthquake Event Report

Region Name: Great Salt Lake Fault

Earthquake Scenario: Great Salt Lake Fault Earthquake Mw 7.0

Print Date: December 22, 2009

Totals only reflect data for those census tracts/blocks included in the user's study region.

Disclaimer:

The estimates of social and economic impacts contained in this report were produced using HAZUS loss estimation methodology software which is based on current scientific and engineering knowledge. There are uncertainties inherent in any loss estimation technique. Therefore, there may be significant differences between the modeled results contained in this report and the actual social and economic losses following a specific earthquake. These results can be improved by using enhanced inventory, geotechnical, and observed ground motion data.

Table of Contents

Section	Page #
General Description of the Region	3
Building and Lifeline Inventory	4
Building Inventory	
Critical Facility Inventory	
Transportation and Utility Lifeline Inventory	
Earthquake Scenario Parameters	6
Direct Earthquake Damage	7
Buildings Damage	
Critical Facilities Damage	
Transportation and Utility Lifeline Damage	
Induced Earthquake Damage	11
Fire Following Earthquake	
Debris Generation	
Social Impact	12
Shelter Requirements	
Casualties	
Economic Loss	13
Building Losses	
Transportation and Utility Lifeline Losses	
Long-term Indirect Economic Impacts	
Appendix A: County Listing for the Region	
Appendix B: Regional Population and Building Value Data	

General Description of the Region

HAZUS is a regional earthquake loss estimation model that was developed by the Federal Emergency Management Agency and the National Institute of Building Sciences. The primary purpose of HAZUS is to provide a methodology and software application to develop earthquake losses at a regional scale. These loss estimates would be used primarily by local, state and regional officials to plan and stimulate efforts to reduce risks from earthquakes and to prepare for emergency response and recovery.

The earthquake loss estimates provided in this report was based on a region that includes 29 county(ies) from the following state(s):

Utah

Note:

Appendix A contains a complete listing of the counties contained in the region.

The geographical size of the region is 84,798.76 square miles and contains 496 census tracts. There are over 773 thousand households in the region and has a total population of 2,474,258 people (2000 Census Bureau data). The distribution of population by State and County is provided in Appendix B.

There are an estimated 653 thousand buildings in the region with a total building replacement value (excluding contents) of 131,629 (millions of dollars). Approximately 95.00 % of the buildings (and 0.00% of the building value) are associated with residential housing.

The replacement value of the transportation and utility lifeline systems is estimated to be 54,677 and 9,370 (millions of dollars), respectively.

Building and Lifeline Inventory

Building Inventory

HAZUS estimates that there are 653 thousand buildings in the region which have an aggregate total replacement value of 131,629 (millions of dollars). Appendix B provides a general distribution of the building value by State and County.

In terms of building construction types found in the region, wood frame construction makes up 46% of the building inventory. The remaining percentage is distributed between the other general building types.

Critical Facility Inventory

HAZUS breaks critical facilities into two (2) groups: essential facilities and high potential loss (HPL) facilities. Essential facilities include hospitals, medical clinics, schools, fire stations, police stations and emergency operations facilities. High potential loss facilities include dams, levees, military installations, nuclear power plants and hazardous material sites.

For essential facilities, there are 56 hospitals in the region with a total bed capacity of 6,868 beds. There are 1,076 schools, 358 fire stations, 133 police stations and 7 emergency operation facilities. With respect to HPL facilities, there are 599 dams identified within the region. Of these, 212 of the dams are classified as 'high hazard'. The inventory also includes 711 hazardous material sites, 0 military installations and 0 nuclear power plants.

<u>Transportation and Utility Lifeline Inventory</u>

Within HAZUS, the lifeline inventory is divided between transportation and utility lifeline systems. There are seven (7) transportation systems that include highways, railways, light rail, bus, ports, ferry and airports. There are six (6) utility systems that include potable water, wastewater, natural gas, crude & refined oil, electric power and communications. The lifeline inventory data are provided in Tables 1 and 2.

The total value of the lifeline inventory is over 64,047.00 (millions of dollars). This inventory includes over 8,874 kilometers of highways, 3,009 bridges, 242,427 kilometers of pipes.

Table 1: Transportation System Lifeline Inventory

System	Component	# locations/ # Segments	Replacement value (millions of dollars)
Highway	Bridges	3,009	3,453.80
	Segments	1,303	46,184.60
	Tunnels	4	2.00
		Subtotal	49,640.40
Railways	Bridges	33	3.90
	Facilities	12	32.00
	Segments	1,485	2,821.00
	Tunnels	0	0.00
		Subtotal	2,856.90
Light Rail	Bridges	0	0.00
•	Facilities	24	63.90
	Segments	24	37.20
	Tunnels	0	0.00
		Subtotal	101.10
Bus	Facilities	10	10.70
		Subtotal	10.70
Ferry	Facilities	2	2.70
,		Subtotal	2.70
Port	Facilities	0	0.00
		Subtotal	0.00
Airport	Facilities	30	319.50
por t	Runways	46	1,746.30
		Subtotal	2,065.90
		Total	54,677.60

Table 2: Utility System Lifeline Inventory

System	Component	# Locations / Segments	Replacement value (millions of dollars)
Potable Water	Distribution Lines	NA	2,948.60
	Facilities	2	65.30
	Pipelines	0	0.00
		Subtotal	3,013.90
Waste Water	Distribution Lines	NA	1,769.20
	Facilities	56	3,655.00
	Pipelines	0	0.00
		Subtotal	5,424.20
Natural Gas	Distribution Lines	NA	1,179.50
	Facilities	8	8.50
	Pipelines	957	2,089.80
		Subtotal	3,277.80
Oil Systems	Facilities	31	3.00
	Pipelines	465	733.60
		Subtotal	736.60
Electrical Power	Facilities	26	2,802.80
		Subtotal	2,802.80
Communication	Facilities	128	12.50
		Subtotal	12.50
		Total	15,267.90

Earthquake Scenaric

HAZUS uses the following set of information to define the earthquake parameters used for the earthquake loss estimate provided in this report.

Scenario Name Great Salt Lake Fault Earthquake Mw 7.0

Type of Earthquake User-defined

Fault Name NA
Historical Epicenter ID # NA
Probabilistic Return Period NA
Longitude of Epicenter NA
Latitude of Epicenter NA
Earthquake Magnitude 7.00
Depth (Km) NA

Rupture Length (Km) NA

Rupture Orientation (degrees) NA

Attenuation Function NA

Building Damage

Building Damage

HAZUS estimates that about 19,782 buildings will be at least moderately damaged. This is over 3.00 % of the total number of buildings in the region. There are an estimated 103 buildings that will be damaged beyond repair. The definition of the 'damage states' is provided in Volume 1: Chapter 5 of the HAZUS technical manual. Table 3 below summaries the expected damage by general occupancy for the buildings in the region. Table 4 summaries the expected damage by general building type.

Table 3: Expected Building Damage by Occupancy

	None		Slight		Moderat	te	Extensiv	re	Complete	
	Count	(%)	Count	(%)	Count	(%)	Count	(%)	Count	(%)
Agriculture	382	0.07	79	0.12	52	0.29	9	0.54	0	0.41
Commercial	18,611	3.27	1,758	2.76	641	3.56	67	4.00	4	3.99
Education	733	0.13	86	0.13	55	0.30	10	0.59	1	0.95
Government	1,487	0.26	198	0.31	155	0.86	29	1.71	2	1.50
Industrial	5,966	1.05	943	1.48	444	2.47	45	2.68	3	2.41
Other Residential	59,990	10.53	11,429	17.95	4,310	23.93	360	21.58	17	16.13
Religion	2,297	0.40	302	0.47	180	1.00	28	1.68	3	2.52
Single Family	480,319	84.30	48,860	76.76	12,173	67.59	1,121	67.22	75	72.08
Total	569,786		63,655		18,010		1,668		104	

Table 4: Expected Building Damage by Building Type (All Design Levels)

	None	None		None Slight		Modera	ite	Extensive		Complete	
	Count	(%)	Count	(%)	Count	(%)	Count	(%)	Count	(%)	
Wood	284,067	49.86	16112	25.31	522	2.90	106	6.34	24	23.29	
Steel	5,007	0.88	674	1.06	469	2.61	63	3.76	4	4.29	
Concrete	4,382	0.77	515	0.81	253	1.40	31	1.85	2	1.83	
Precast	3,285	0.58	233	0.37	148	0.82	24	1.45	1	1.34	
RM	114,313	20.06	4497	7.06	1,088	6.04	88	5.28	8	7.30	
URM	133,576	23.44	39102	61.43	14,422	80.08	1,266	75.92	60	57.68	
MH	25,157	4.42	2521	3.96	1,108	6.15	90	5.40	4	4.27	
Total	569,786		63,655		18,010		1,668		104		

*Note:

RM Reinforced Masonry
URM Unreinforced Masonry
MH Manufactured Housing

Essential Facility Damage

Before the earthquake, the region had 6,868 hospital beds available for use. On the day of the earthquake, the model estimates that only 6,661 hospital beds (97.00%) are available for use by patients already in the hospital and those injured by the earthquake. After one week, 100.00% of the beds will be back in service. By 30 days, 100.00% will be operational.

Table 5: Expected Damage to Essential Facilities

			# Facilities	
Classification	Total	At Least Moderate Damage > 50%	Complete Damage > 50%	With Functionality > 50% on day 1
Hospitals	56	0	0	56
Schools	1,076	0	0	1,076
EOCs	7	0	0	7
PoliceStations	133	0	0	133
FireStations	358	0	0	357

<u>Transportation and Utility Lifeline Damage</u>

Table 6 provides damage estimates for the transportation system.

Table 6: Expected Damage to the Transportation Systems

				Number of Location	ons_	
System	Component	Locations/	With at Least	With Complete	With Fun	ctionality > 50 %
		Segments	Mod. Damage	Damage	After Day 1	After Day 7
Highway	Segments	1,303	0	0	1,303	1,303
	Bridges	3,009	14	4	2,995	2,999
	Tunnels	4	0	0	4	4
Railways	Segments	1,485	0	0	1,485	1,485
	Bridges	33	0	0	33	33
	Tunnels	0	0	0	0	0
	Facilities	12	0	0	12	12
Light Rail	Segments	24	0	0	24	24
	Bridges	0	0	0	0	0
	Tunnels	0	0	0	0	0
	Facilities	24	0	0	24	24
Bus	Facilities	10	0	0	10	10
Ferry	Facilities	2	0	0	2	2
Port	Facilities	0	0	0	0	0
Airport	Facilities	30	0	0	30	30
	Runways	46	0	0	46	46

Note: Roadway segments, railroad tracks and light rail tracks are assumed to be damaged by ground failure only. If ground failure maps are not provided, damage estimates to these components will not be computed.

Tables 7-9 provide information on the damage to the utility lifeline systems. Table 7 provides damage to the utility system facilities. Table 8 provides estimates on the number of leaks and breaks by the pipelines of the utility systems. For electric power and potable water, HAZUS performs a simplified system performance analysis. Table 9 provides a summary of the system performance information.

Table 7 : Expected Utility System Facility Damage

	# of Locations								
System	Total #	With at Least	With Complete	with Function	with Functionality > 50 %				
		Moderate Damage	Damage	After Day 1	After Day 7				
Potable Water	2	0	0	2	2				
Waste Water	56	1	0	49	56				
Natural Gas	8	0	0	8	8				
Oil Systems	31	0	0	31	31				
Electrical Power	26	0	0	26	26				
Communication	128	0	0	128	128				

Table 8 : Expected Utility System Pipeline Damage (Site Specific)

System	Total Pipelines Length (kms)	Number of Leaks	Number of Breaks
Potable Water	147,432	1121	537
Waste Water	88,459	887	425
Natural Gas	4,166	7	11
Oil	2,370	3	4

Table 9: Expected Potable Water and Electric Power System Performance

	Total # of Number of Households without Service					
	Households	At Day 1	At Day 3	At Day 7	At Day 30	At Day 90
Potable Water	772 252	66,008	48,195	19,129	0	0
Electric Power	773,352	0	0	0	0	0

Induced Earthquake Damage

Fire Following Earthquake

Fires often occur after an earthquake. Because of the number of fires and the lack of water to fight the fires, they can often burn out of control. HAZUS uses a Monte Carlo simulation model to estimate the number of ignitions and the amount of burnt area. For this scenario, the model estimates that there will be 57 ignitions that will burn about 1.76 sq. mi 0.00 % of the region's total area.) The model also estimates that the fires will displace about 6,279 people and burn about 295 (millions of dollars) of building value.

Debris Generation

HAZUS estimates the amount of debris that will be generated by the earthquake. The model breaks the debris into two general categories: a) Brick/Wood and b) Reinforced Concrete/Steel. This distinction is made because of the different types of material handling equipment required to handle the debris.

The model estimates that a total of 1.080 million tons of debris will be generated. Of the total amount, Brick/Wood comprises 68.00% of the total, with the remainder being Reinforced Concrete/Steel. If the debris tonnage is converted to an estimated number of truckloads, it will require 43,240,000 truckloads (@25 tons/truck) to remove the debris generated by the earthquake.

Social Impact

Shelter Requirement

HAZUS estimates the number of households that are expected to be displaced from their homes due to the earthquake and the number of displaced people that will require accommodations in temporary public shelters. The model estimates 660 households to be displaced due to the earthquake. Of these, 488 people (out of a total population of 2,474,258) will seek temporary shelter in public shelters.

Casualties

HAZUS estimates the number of people that will be injured and killed by the earthquake. The casualties are broken down into four (4) severity levels that describe the extent of the injuries. The levels are described as follows;

- · Severity Level 1: Injuries will require medical attention but hospitalization is not needed.
- · Severity Level 2: Injuries will require hospitalization but are not considered life-threatening
- · Severity Level 3: Injuries will require hospitalization and can become life threatening if not promptly treated.
- · Severity Level 4: Victims are killed by the earthquake.

The casualty estimates are provided for three (3) times of day: 2:00 AM, 2:00 PM and 5:00 PM. These times represent the periods of the day that different sectors of the community are at their peak occupancy loads. The 2:00 AM estimate considers that the residential occupancy load is maximum, the 2:00 PM estimate considers that the educational, commercial and industrial sector loads are maximum and 5:00 PM represents peak commute time.

Table 10 provides a summary of the casualties estimated for this earthquake

Table 10: Casualty Estimates

		Level 1	Level 2	Level 3	Level 4
2 AM	Commercial	4	0	0	0
	Commuting	0	0	0	0
	Educational	0	0	0	0
	Hotels	3	0	0	0
	Industrial	8	1	0	0
	Other-Residential	113	11	1	1
	Single Family	329	33	2	3
	Total	457	46	3	4
2 PM	Commercial	220	25	2	3
	Commuting	1	1	1	0
	Educational	87	13	1	2
	Hotels	1	0	0	0
	Industrial	59	8	1	1
	Other-Residential	22	2	0	0
	Single Family	64	7	0	1
	Total	453	56	5	7
5 PM	Commercial	171	21	1	3
	Commuting	24	29	52	10
	Educational	9	1	0	0
	Hotels	1	0	0	O
	Industrial	37	5	0	1
	Other-Residential	44	5	0	O
	Single Family	130	13	1	1
	Total	416	74	55	15

Economic Loss

The total economic loss estimated for the earthquake is 1,923.47 (millions of dollars), which includes building and lifeline related losses based on the region's available inventory. The following three sections provide more detailed information about these losses.

Building-Related Losses

The building losses are broken into two categories: direct building losses and business interruption losses. The direct building losses are the estimated costs to repair or replace the damage caused to the building and its contents. The business interruption losses are the losses associated with inability to operate a business because of the damage sustained during the earthquake. Business interruption losses also include the temporary living expenses for those people displaced from their homes because of the earthquake.

The total building-related losses were 1,684.63 (millions of dollars); 25 % of the estimated losses were related to the business interruption of the region. By far, the largest loss was sustained by the residential occupancies which made up over 45 % of the total loss. Table 11 below provides a summary of the losses associated with the building damage.

Table 11: Building-Related Economic Loss Estimates

(Millions of dollars)

Category	Area	Single Family	Other Residential	Commercial	Industrial	Others	Total
Income Los	es						
	Wage	0.00	7.48	34.18	4.44	17.15	63.25
	Capital-Related	0.00	3.24	30.22	2.73	4.00	40.19
	Rental	20.55	30.40	35.03	4.49	5.99	96.47
	Relocation	75.23	18.45	45.22	25.36	58.51	222.77
	Subtotal	95.79	59.57	144.66	37.02	85.65	422.68
Capital Sto	ck Loses						
	Structural	82.89	22.89	40.68	24.66	44.92	216.04
	Non_Structural	250.42	101.57	124.06	95.62	110.58	682.26
	Content	107.30	32.38	82.13	71.76	53.31	346.88
	Inventory	0.00	0.00	4.05	12.15	0.57	16.77
	Subtotal	440.61	156.84	250.92	204.20	209.37	1,261.95
	Total	536.40	216.40	395.58	241.21	295.03	1,684.63

Transportation and Utility Lifeline Losses

For the transportation and utility lifeline systems, HAZUS computes the direct repair cost for each component only. There are no losses computed by HAZUS for business interruption due to lifeline outages. Tables 12 & 13 provide a detailed breakdown in the expected lifeline losses.

HAZUS estimates the long-term economic impacts to the region for 15 years after the earthquake. The model quantifies this information in terms of income and employment changes within the region. Table 14 presents the results of the region for the given earthquake.

Table 12: Transportation System Economic Losses

(Millions of dollars)

System	Component	Inventory Value	Economic Loss	Loss Ratio (%)
Highway	Segments	46,184.62	\$32.45	0.07
	Bridges	3,453.84	\$43.48	1.26
	Tunnels	1.96	\$0.00	0.00
	Subtotal	49640.40	75.90	
Railways	Segments	2,821.00	\$1.77	0.06
	Bridges	3.92	\$0.00	0.05
	Tunnels	0.00	\$0.00	0.00
	Facilities	31.96	\$2.41	7.54
	Subtotal	2856.90	4.20	
Light Rail	Segments	37.15	\$0.01	0.02
	Bridges	0.00	\$0.00	0.00
	Tunnels	0.00	\$0.00	0.00
	Facilities	63.91	\$6.44	10.08
	Subtotal	101.10	6.50	
Bus	Facilities	10.68	\$0.44	4.10
	Subtotal	10.70	0.40	
Ferry	Facilities	2.66	\$0.00	0.11
	Subtotal	2.70	0.00	
Port	Facilities	0.00	\$0.00	0.00
	Subtotal	0.00	0.00	
Airport	Facilities	319.53	\$8.77	2.75
	Runways	1,746.34	\$1.32	0.08
	Subtotal	2065.90	10.10	
	Total	54677.60	97.10	

Table 13: Utility System Economic Losses

(Millions of dollars)

System	Component	Inventory Value	Economic Loss	Loss Ratio (%)
Potable Water	Pipelines	0.00	\$0.00	0.00
	Facilities	65.30	\$0.84	1.29
	Distribution Lines	2,948.60	\$7.61	0.26
	Subtotal	3,013.92	\$8.45	
Waste Water	Pipelines	0.00	\$0.00	0.00
	Facilities	3,655.00	\$73.18	2.00
	Distribution Lines	1,769.20	\$6.02	0.34
	Subtotal	5,424.20	\$79.20	
Natural Gas	Pipelines	2,089.80	\$0.12	0.01
	Facilities	8.50	\$0.03	0.32
	Distribution Lines	1,179.50	\$6.43	0.55
	Subtotal	3,277.83	\$6.58	
Oil Systems	Pipelines	733.60	\$0.02	0.00
	Facilities	3.00	\$0.06	1.84
	Subtotal	736.60	\$0.08	
Electrical Power	Facilities	2,802.80	\$47.05	1.68
	Subtotal	2,802.80	\$47.05	
Communication	Facilities	12.50	\$0.37	2.93
	Subtotal	12.54	\$0.37	
	Total	15,267.88	\$141.73	

Table 14. Indirect Economic Impact with outside aid (Employment as # of people and Income in millions of \$)

	LOSS	Total	%
First Year			
	Employment Impact	32,239	4.15
	Income Impact	69	0.24
Second Year			
	Employment Impact	13,027	1.68
	Income Impact	14	0.05
Third Year			
	Employment Impact	312	0.04
	Income Impact	(29)	-0.10
Fourth Year			
	Employment Impact	15	0.00
	Income Impact	(42)	-0.14
Fifth Year			
	Employment Impact	0	0.00
	Income Impact	(42)	-0.15
Years 6 to 15			
	Employment Impact	0	0.00
	Income Impact	(42)	-0.15


Appendix A: County Listing for the Region




Appendix B: Regional Population and Building Value Data

State	County Name F		Building	Building Value (millions of dollars)		
		Population	Residential	Non-Residential	Total	
Utah						
	Beaver	6,295	252	89	341	
	Box Elder	45,659	1,658	687	2,346	
	Cache	100,585	3,382	1,703	5,085	
	Carbon	19,947	825	395	1,220	
	Daggett	884	74	18	92	
	Davis	270,344	10,230	3,870	14,101	
	Duchesne	15,233	496	248	744	
	Emery	10,885	403	142	546	
	Garfield	4,957	276	94	370	
	Grand	8,891	350	195	546	
	Iron	37,498	1,323	741	2,065	
	Juab	9,240	291	190	481	
	Kane	6,385	323	127	450	
	Millard	12,713	447	233	681	
	Morgan	7,910	305	139	444	
	Piute	1,439	69	24	93	
	Rich	2,327	249	38	288	
	Salt Lake	962,837	39,526	18,636	58,162	
	San Juan	14,341	443	164	608	
	Sanpete	24,037	708	387	1,095	
	Sevier	19,623	697	315	1,013	
	Summit	35,804	2,598	708	3,307	
	Tooele	50,184	1,782	564	2,347	
	Uintah	26,973	851	460	1,312	
	Utah	429,727	9,780	6,285	16,065	
	Wasatch	18,879	0	89	89	
	Washington	113,489	3,900	1,839	5,739	
	Wayne	2,590	115	38	154	
	Weber	214,582	8,462	3,369	11,831	
Total State		2,474,258	89,815	41,787	131,615	
Total Region		2,474,258	89,815	41,787	131,615	


Direct Building Economic Loss - Earthquake Scenario: Great Salt Lake Segment, UT



Estimated Displaced Households & Short Term Public Shelter Needs - Earthquake Scenario: Great Salt Lake Segment, UT



Distribution of Elderly, Impaired Hospitals (Day 1) & Hospital Bed Availability - Earthquake Scenario: Great Salt Lake Segment, UT



M 7.0 Great Salt Lake Segment Earthquake

Highway Damage

Damage is expressed as the probability that a given bridge or highway segment will realize at least moderate damage.

iiipact		Bridge impact	
	Low	•	Low
	Moderate	•	Moderate
	High	•	High

Impaired Hospitals (Day 1)

Damage is expressed as the probablility that a given hospital will realize at least moderate damage




Major Roadway


High

County	Hospital Beds	Beds Available	Requiring Hospital Treatment 2pm
Salt Lake	3,440	3,281	41
Juab	31	31	0
Weber	655	628	3
Cache	158	158	0
Duchesne	42	42	0
Davis	468	429	14
Millard	40	40	0
Utah	1,013	1,011	0
Sanpete	44	44	0
Wasatch	20	20	0
Box Elder	107	107	0
Tooele	468	468	3
Total	6.486	6.259	61






Electrical, Natural Gas & Oil Facility Damage - Earthquake Scenario: Great Salt Lake Segment, UT



Estimated Building Inspection Needs - Earthquake Scenario: Great Salt Lake Segment, UT




M 7.0 Great Salt Lake Segment Earthquake


	Estimated # of Structures	Estimated # of Inspectors Needed	
Red (Complete)	104	1	
Yellow (Extensive)	1,686	23	
Light Green (Slight/ Moderate)	81,658	545	
Total	83,448	569	

*Estimated number of inspectors needed to complete inspections in 30 days.


- Red Tag
 (Complete Damage)
- Yellow Tag
 (Extensive Damage)
- Green Tag
 (Slight/Moderate Damage)

*1 Dot = 10 (by census tract)







Estimated Concrete, Steel Debris & Highway Damage - Earthquake Scenario: Great Salt Lake Segment, UT



Demographic Distribution & Highway Damage - Earthquake Scenario: Great Salt Lake Segment, UT



Estimated Highway Infrastructure Damage - Earthquake Scenario: Great Salt Lake Segment, UT



M 7.0 Great Salt Lake Segment Earthquake

Highway Damage


Damage is expressed as the probability that a given bridge or highway segment will realize at least moderate damage.

			-
	Segment act	•	Roadway e Impact
	Low	• L	ow
	Moderate	o 1	/loderate
	High	• н	ligh
County	Total # of Bridges	# Bridges Needing Priority Inspection	*# of Bridge Engineers Needed
Utah	314	0	0
Box Elder	230	0	0


County	Total # of Bridges	Needing Priority Inspection	*# of Bridge Engineers Needed
Utah	314	0	0
Box Elder	230	0	0
Wasatch	24	0	0
Tooele	54	9	1
Salt Lake	608	36	5
Weber	141	4	1
Summit	156	0	0
Morgan	80	0	0
Davis	130	4	1
Total	1,737	53	8

*Based on assuming that 2 engineers can inspect 5 bridges a day for 3 days.





Impaired Hospitals (Day 1), Hospital Availability & Highway Functionality - Earthquake Scenario: Great Salt Lake Segment, UT



M 7.0 Great Salt Lake Segment Earthquake

Highway Damage

or highway segment will realize at least moderate damage

			J p
	Low	•	Low
	Moderate	•	Moderate


Impaired Hospitals (Day 1)

Ш	Low
\blacksquare	Moderate


Injuries

County	Hospital Beds	Beds Available	Requiring Hospital Treatment 2pm
Salt Lake	3,440	3,281	41
Juab	31	31	0
Weber	655	628	3
Cache	158	158	0
Duchesne	42	42	0
Davis	468	429	14
Millard	40	40	0
Utah	1,013	1,011	0
Sanpete	44	44	0
Wasatch	20	20	0
Box Elder	107	107	0
Tooele	468	468	3
Total	6.486	6.259	61






Water Line, Sewage Treatment Facility Distribution and Liquefaction - Earthquake Scenario: Great Salt Lake Segment, UT



Potential Search & Rescue Needs - Earthquake Scenario: Great Salt Lake Segment, UT



M 7.0 Great Salt Lake Segment Earthquake

Impaired Hospitals (Day 1)

Damage is expressed as the probablility that a given hospital will realize at least moderate damage. Low

Moderate

High

PGA (% g's)

< 0.02

0.02 - 0.04

0.09 - 0.18


1 Dot = 1 Life Threatening Injury (Severity Level 3)

*Severity Level 3 is defined as injuries that require hospitalization and can become life threatening if not promptly treated.

Structure Type	Red (Complete)	Collapse Rates for Complete Damage	Total Collapse
Wood	24	3%	1
Steel	4	6%	0
Concrete	2	10%	0
Precast	1	13%	0
Reinforced Masonry	8	10%	1
Unreinforced Masonry	60	15%	9
Manufactured Housing	4	3%	0
Total	102		11

Requiring Hospital	Immediate Life	
Treatment	Threatening Injuries	
175	62	





Correctional and Daycare Facilities, Impaired Hospitals (Day 1) and Highway Functionality - Earthquake Scenario: Great Salt Lake Segment, UT

